

# Wikiprint Book

**Title:** InterTrac Links

**Subject:** TechTIDE-Wiki - InterTrac

**Version:** 1

**Date:** 08/02/25 23:13:43

## Table of Contents

<b>InterTrac Links</b>	<b>3</b>
Link Syntax	3
Examples	3
List of Active InterTrac Prefixes	4

## [InterTrac Links](#)

Trac supports a convenient way to refer to resources of other Trac servers using Wiki markup. An InterTrac link can be seen as a scoped [TracLink](#). It is used for referring to a Trac resource located in another Trac environment.

### Link Syntax

Simply use the name of the other Trac environment as a prefix, followed by a colon, ending with the resource located in the other environment:

```
<target_environment>:<TracLinks>
```

The other resource is specified using a regular TracLink, of any flavor.

That target environment name is either the real name of the environment or an alias. The aliases are defined in the `trac.ini` file, see below. The prefix is case insensitive.

If the [InterTrac](#) link is enclosed in square brackets, like `[th:WikiExtrasPlugin]`, the [InterTrac](#) prefix is removed in the displayed link like a normal link resolver would be. For example, the above would be displayed as `WikiExtrasPlugin`.

For convenience, there is also an alternate short-hand form, where an alias can be used as an immediate prefix for the identifier of a ticket, changeset or report, eg `#T234`, `[T1508]`, `[trac 1508]`.

### Examples

The only prefix defined by default is `trac`, which points to `trac.edgewall.org`. Additional prefixes can be specified in the `intertrac` section of [TracIni](#). For example:

```
[intertrac]
# -- Example of setting up an alias:
t = trac

# -- Link to an external Trac:
genshi.title = Edgewall's Trac for Genshi
genshi.url = http://genshi.edgewall.org
```

The `.url` is mandatory and is used for locating the other Trac. It can be a relative URL when the Trac environment is located on the same server.

The `.title` information is used in a tooltip, ie when hovering the cursor over an [InterTrac](#) link.

Now, given the above configuration, one could create the following links:

- to this [InterTrac](#) page:
  - `trac:wiki:InterTrac` [trac:wiki:InterTrac](#)
  - `t:wiki:InterTrac` [t:wiki:InterTrac](#)
  - `genshi:InterTrac` [genshi:InterTrac](#)
  - Keys are case insensitive: `T:wiki:InterTrac` `T:wiki:InterTrac`
- to the ticket [#234](#):
  - `trac:ticket:234` [trac:ticket:234](#)
  - `trac:#234` [trac:#234](#)
  - `genshi:#234` [genshi:#234](#)
  - `#T234` [#T234](#)
- to the changeset [\[1912\]](#):
  - `trac:changeset:1912` [trac:changeset:1912](#)
  - `[T1912]` [\[T1912\]](#)
- to the log range [\[3300:3330\]](#):
  - `trac:log:@3300:3330` [trac:log:@3300:3330](#)
  - `[trac 3300:3330]` [\[trac 3300:3330\]](#)
- finally, to link to the start page of a remote trac, simply use its prefix followed by ':', inside an explicit link. Example: `[th: Trac Hacks]` (note that the *remote* Trac has to run Trac >= 0.11 for this to work)

The generic form `intertrac_prefix:module:id` is translated to the corresponding URL `<remote>/module/id`. Shorthand links are specific to some modules (e.g. `#T234` is processed by the ticket module). For the rest (`intertrac_prefix:something`), we rely on the [quick jump](#) facility of the remote Trac.

## List of Active [InterTrac](#) Prefixes

The following [InterTrac](#) prefixes are available on this site:

<i>Prefix</i>	<i>Trac Site</i>
<a href="#">trac</a>	<a href="#">The Trac Project</a>

---

See also: [TracLinks](#), [InterWiki](#)