

TracAdmin

Trac is distributed with a powerful command-line configuration tool. This tool can be used to configure and customize your Trac installation to better fit your needs.

Some of the configurations can also be performed via the web administration module.

Usage

For nearly every `trac-admin` command, the first argument must be the path to the TracEnvironment:

```
$ trac-admin /path/to/projenv wiki list
```

The only exception is for the `help` command, but even in this case, if you omit the environment you will only get a very succinct list of commands (`help` and `initenv`), the same list you would get when invoking `trac-admin` alone. `trac-admin --version` will tell you about the Trac version (e.g. 1.2) corresponding to the program.

To get a comprehensive list of the available command and sub-command, specify the path to an environment:

```
$ trac-admin /path/to/projenv
```

Some commands have more detailed help, which you can access by specifying the command's name as a subcommand for `help`:

```
$ trac-admin /path/to/projenv <command>
```

When an error occurs in a `trac-admin` command the return value will be 2 and error messages are printed to `stderr`.

trac-admin <targetdir> initenv

This subcommand is very important as is the one used to create a TracEnvironment in the specified `<targetdir>`. That directory must not exist prior to the call.

```
initenv [<projectname> <db> [<repostype> <repospath>]]
```

Create and initialize a new environment

If no arguments are given, then the required parameters are requested interactively unless the optional argument `--config` is specified.

One or more optional arguments `--inherit=PATH` can be used to specify the "[inherit] file" option at environment creation time, so that only the options not already specified in one of the global configuration files are written to the `conf/trac.ini` file of the newly created environment. Relative paths are resolved relative to the "conf" directory of the new environment.

The optional argument `--config=PATH` can be used to specify a configuration file that is used to populate the environment configuration. The arguments `<projectname>`, `<db>` and any other arguments passed in the invocation are

optional, but if specified will override values in the configuration file.

It supports the `--inherit` option, which specifies a global configuration file for sharing settings between several environments. You can also inherit from a shared configuration afterwards, by setting the `[inherit]` file option in the `conf/trac.ini` file in your newly created environment. The advantage of specifying the inherited configuration file at environment creation time is that only the options *not* specified in the global configuration file will be written to the environment's `conf/trac.ini` file. See [TracIni#GlobalConfiguration](#).

Interactive Mode

`trac-admin` starts in interactive mode when the environment path is the only argument. Commands can then be executed on the selected environment using the prompt, which offers tab-completion for non-Windows environments, and when the Python `readline` module is available. It also offers automatic repetition of the last command issued.

Once you are in interactive mode, you can also get help on specific commands or subsets of commands:

For example, to get an explanation of the `resync` command, run:

```
$ resync
```

To get help on all the Wiki-related commands, run:

```
$ wiki
```

Full Command Reference

You will find below the detailed help for all the commands available by default in `trac-admin`. Note that this may not match the list given by `trac-admin <yourenv> help`, as the commands pertaining to components disabled in that environment won't be available and conversely some plugins activated in the environment may add their own commands.

```
help
    Show documentation

initenv [<projectname> <db> [<repostype> <repospath>]]
    Create and initialize a new environment

    If no arguments are given, then the required parameters are requested
    interactively unless the optional argument --config is specified.

    One or more optional arguments --inherit=PATH can be used to specify the
    "[inherit] file" option at environment creation time, so that only the
    options not already specified in one of the global configuration files are
    written to the conf/trac.ini file of the newly created environment.
    Relative paths are resolved relative to the "conf" directory of the new
    environment.

    The optional argument --config=PATH can be used to specify a configuration
    file that is used to populate the environment configuration. The arguments
```

<projectname>, <db> and any other arguments passed in the invocation are optional, but if specified will override values in the configuration file.

attachment add <realm:id> <path> [author] [description]

Attach a file to a resource

The resource is identified by its realm and identifier. The attachment will be named according to the base name of the file.

attachment export <realm:id> <name> [destination]

Export an attachment from a resource to a file or stdout

The resource is identified by its realm and identifier. If no destination is specified, the attachment is output to stdout.

attachment list <realm:id>

List attachments of a resource

The resource is identified by its realm and identifier.

attachment remove <realm:id> <name>

Remove an attachment from a resource

The resource is identified by its realm and identifier.

changeset added <repos> <rev> [rev] [...]

Notify trac about changesets added to a repository

This command should be called from a post-commit hook. It will trigger a cache update and notify components about the addition.

changeset modified <repos> <rev> [rev] [...]

Notify trac about changesets modified in a repository

This command should be called from a post-revprop hook after revision properties like the commit message, author or date have been changed. It will trigger a cache update for the given revisions and notify components about the change.

component add <name> [owner]

Add a new component

component chown <name> <owner>

Change component ownership

component list

Show available components

component remove <name>

Remove/uninstall a component

component rename <name> <newname>

```

    Rename a component

config get <section> <option>

    Get the value of the given option in "trac.ini"

config remove <section> <option>

    Remove the specified option from "trac.ini"

config set <section> <option> <value>

    Set the value for the given option in "trac.ini"

deploy <directory>

    Extract static resources from Trac and all plugins

hotcopy <backupdir> [--no-database]

    Make a hot backup copy of an environment

    The database is backed up to the 'db' directory of the destination, unless
    the --no-database option is specified.

milestone add <name> [due]

    Add milestone

milestone completed <name> <completed>

    Set milestone complete date

    The <completed> date must be specified in the "d MMM yyyy HH:mm:ss" or
    "YYYY-MM-DDThh:mm:ss±hh:mm" (ISO 8601) format. Alternatively, "now" can be
    used to set the completion date to the current time. To remove the
    completion date from a milestone, specify an empty string ("").

milestone due <name> <due>

    Set milestone due date

    The <due> date must be specified in the "d MMM yyyy HH:mm:ss" or "YYYY-MM-
    DDThh:mm:ss±hh:mm" (ISO 8601) format. Alternatively, "now" can be used to
    set the due date to the current time. To remove the due date from a
    milestone, specify an empty string ("").

milestone list

    Show milestones

milestone remove <name>

    Remove milestone

milestone rename <name> <newname>

    Rename milestone

permission add <user> <action> [action] [...]

```

```

    Add a new permission rule

permission export [file]

    Export permission rules to a file or stdout as CSV

permission import [file]

    Import permission rules from a file or stdin as CSV

permission list [user]

    List permission rules

permission remove <user> <action> [action] [...]

    Remove a permission rule

priority add <value>

    Add a priority value option

priority change <value> <newvalue>

    Change a priority value

priority list

    Show possible ticket priorities

priority order <value> up|down

    Move a priority value up or down in the list

priority remove <value>

    Remove a priority value

repository add <repos> <dir> [type]

    Add a source repository

repository alias <name> <target>

    Create an alias for a repository

repository list

    List source repositories

repository remove <repos>

    Remove a source repository

repository resync <repos> [rev]

    Re-synchronize trac with repositories

    When [rev] is specified, only that revision is synchronized. Otherwise, the
    complete revision history is synchronized. Note that this operation can
    take a long time to complete. If synchronization gets interrupted, it can
    be resumed later using the `sync` command.

```

To synchronize all repositories, specify "*" as the repository.

```
repository set <repos> <key> <value>
```

Set an attribute of a repository

The following keys are supported: alias, description, dir, hidden, name, sync_per_request, type, url

```
repository sync <repos> [rev]
```

Resume synchronization of repositories

It works like `resync`, except that it doesn't clear the already synchronized changesets, so it's a better way to resume an interrupted `resync`.

See `resync` help for detailed usage.

```
resolution add <value>
```

Add a resolution value option

```
resolution change <value> <newvalue>
```

Change a resolution value

```
resolution list
```

Show possible ticket resolutions

```
resolution order <value> up|down
```

Move a resolution value up or down in the list

```
resolution remove <value>
```

Remove a resolution value

```
session add <sid[:0|1]> [name] [email]
```

Create a session for the given sid

Populates the name and email attributes for the given session. Adding a suffix ':0' to the sid makes the session unauthenticated, and a suffix ':1' makes it authenticated (the default if no suffix is specified).

```
session delete <sid[:0|1]> [...]
```

Delete the session of the specified sid

An sid suffix ':0' operates on an unauthenticated session with the given sid, and a suffix ':1' on an authenticated session (the default). Specifying the sid 'anonymous' will delete all anonymous sessions.

```
session list [sid[:0|1]] [...]
```

List the name and email for the given sids

Specifying the sid 'anonymous' lists all unauthenticated sessions, and 'authenticated' all authenticated sessions. '*' lists all sessions, and is

the default if no sids are given.

An sid suffix ':0' operates on an unauthenticated session with the given sid, and a suffix ':1' on an authenticated session (the default).

`session purge <age>`

Purge anonymous sessions older than the given age or date

Age may be specified as a relative time like "90 days ago", or as a date in the "d MMM yyyy HH:mm:ss" or "YYYY-MM-DDThh:mm:ss±hh:mm" (ISO 8601) format.

`session set <name|email|default_handler> <sid[:0|1]> <value>`

Set the name or email attribute of the given sid

An sid suffix ':0' operates on an unauthenticated session with the given sid, and a suffix ':1' on an authenticated session (the default).

`severity add <value>`

Add a severity value option

`severity change <value> <newvalue>`

Change a severity value

`severity list`

Show possible ticket severities

`severity order <value> up|down`

Move a severity value up or down in the list

`severity remove <value>`

Remove a severity value

`ticket remove <number>`

Remove ticket

`ticket_type add <value>`

Add a ticket type

`ticket_type change <value> <newvalue>`

Change a ticket type

`ticket_type list`

Show possible ticket types

`ticket_type order <value> up|down`

Move a ticket type up or down in the list

`ticket_type remove <value>`

Remove a ticket type

```

upgrade [--no-backup]

    Upgrade database to current version

    The database is backed up to the directory specified by [trac] backup_dir
    (the default is 'db'), unless the --no-backup option is specified. The
    shorthand alias -b can also be used to specify --no-backup.

version add <name> [time]

    Add version

version list

    Show versions

version remove <name>

    Remove version

version rename <name> <newname>

    Rename version

version time <name> <time>

    Set version date

    The <time> must be specified in the "d MMM yyyy HH:mm:ss" or "YYYY-MM-
    DDThh:mm:ss±hh:mm" (ISO 8601) format. Alternatively, "now" can be used to
    set the version date to the current time. To remove the date from a
    version, specify an empty string ("").

wiki dump <directory> [page] [...]

    Export wiki pages to files named by title

    Individual wiki page names can be specified after the directory. A name
    ending with a * means that all wiki pages starting with that prefix should
    be dumped. If no name is specified, all wiki pages are dumped.

wiki export <page> [file]

    Export wiki page to file or stdout

wiki import <page> [file]

    Import wiki page from file or stdin

wiki list

    List wiki pages

wiki load <path> [...]

    Import wiki pages from files

    If a given path is a file, it is imported as a page with the name of the
    file. If a path is a directory, all files in that directory are imported.

wiki remove <page>

```



```
Remove wiki page

wiki rename <page> <new_name>

Rename wiki page

wiki replace <path> [...]

Replace the content of wiki pages from files (DANGEROUS!)

This command replaces the content of the last version of one or more wiki
pages with new content. The previous content is lost, and no new entry is
created in the page history. The metadata of the page (time, author) is not
changed either.

If a given path is a file, it is imported as a page with the name of the
file. If a path is a directory, all files in that directory are imported.

WARNING: This operation results in the loss of the previous content and
cannot be undone. It may be advisable to backup the current content using
"wiki dump" beforehand.

wiki upgrade

Upgrade default wiki pages to current version
```

See also: [TracBackup](#), [TracEnvironment](#), [TracIni](#), [?TracMigrate](#)